



2 tubi		3R		scambiatore		20	30	40	50	60	70	80
 7/12°C 27°C d.b. 19°C w.b. 	Potenza frigorifera totale	(E)	W	6	1685	2599	2769	3826	4236	4912	6034	
			W	5	1358	2340	2340	3418	3450	4024	5685	
			W	4	1248	2127	2127	3051	3071	3451	5466	
			W	3	1143	1864	1895	2742	3022	3030	4949	
			W	2	1058	1424	1424	2433	2460	2810	4117	
			W	1	992	1282	1292	2167	2397	2427	3019	
	Potenza frigorifera sensibile	(E)	W	6	1335	2129	2389	2726	3416	3592	4304	
			W	5	1128	1890	1890	2408	2740	3074	4005	
			W	4	988	1617	1697	2121	2331	2611	3866	
			W	3	873	1444	1505	1882	2372	2250	3449	
			W	2	788	1104	1144	1683	1900	1950	2827	
			W	1	722	1032	1122	1467	1857	1687	2059	
	Portata acqua		l/h	6	299	457	487	673	743	860	1065	
			l/h	5	240	411	410	600	606	703	1002	
			l/h	4	219	363	372	534	538	602	963	
			l/h	3	202	326	332	479	527	531	871	
			l/h	2	186	249	249	425	429	489	727	
			l/h	1	173	223	224	377	417	423	534	
	Perdite di carico lato acqua	(E)	kPa	6	3,9	10,5	11,7	25,2	30,0	58,8	34,0	
			kPa	5	2,3	7,5	8,8	19,8	25,9	37,6	30,3	
kPa			4	2,0	6,3	7,3	16,2	17,0	27,7	28,1		
kPa			3	1,7	5,0	5,6	13,0	16,3	21,4	23,0		
kPa			2	1,4	2,7	3,2	10,8	12,9	18,4	16,5		
kPa			1	1,4	2,6	3,0	8,1	10,8	16,9	8,9		
Potenza termica	(E)	W	6	2160	2700	3120	3950	4290	5040	6270		
		W	5	1910	2430	2770	3500	3760	4300	5900		
		W	4	1610	2150	2510	3050	3310	3640	5660		
		W	3	1410	1940	2185	2720	2970	3170	5040		
		W	2	1250	1580	1800	2440	2610	2680	4180		
		W	1	1150	1410	1570	2130	2330	2310	3080		
		Portata acqua		l/h	6	377	470	544	689	747	878	1093
				l/h	5	333	423	483	609	655	749	1027
				l/h	4	280	374	437	531	576	635	987
				l/h	3	246	339	383	474	517	552	887
l/h	2			218	276	314	426	455	466	728		
l/h	1			201	245	274	371	405	402	536		
Perdite di carico lato acqua	(E)	kPa	6	4,9	9,1	11,8	21,6	32,4	50,2	30,4		
		kPa	5	2,8	7,6	9,2	17,4	21,8	38,0	27,1		
		kPa	4	2,4	6,1	8,0	13,7	15,8	28,4	25,1		
		kPa	3	1,7	4,2	6,1	11,2	13,1	21,0	20,0		
		kPa	2	1,4	3,0	4,3	9,3	11,3	15,6	13,9		
		kPa	1	1,2	2,9	3,5	7,3	8,5	12,7	7,7		
Potenza termica	(E)	W	6	2510	3230	3700	4740	5150	6040	7510		
		W	5	2190	2910	3270	4190	4480	5130	7060		
		W	4	1870	2570	2950	3660	3940	4360	6780		
		W	3	1650	2330	2600	3270	3570	3800	6030		
		W	2	1470	1880	2110	2930	3120	3220	5020		
		W	1	1360	1670	1850	2560	2800	2780	3690		
		Portata acqua		l/h	6	299	457	487	673	743	860	1065
				l/h	5	240	411	410	600	606	703	1002
				l/h	4	219	363	372	534	538	602	963
				l/h	3	202	326	332	479	527	531	871
l/h	2			186	249	249	425	429	489	727		
l/h	1			173	223	224	377	417	423	534		
Perdite di carico lato acqua	(E)	kPa	6	3,2	8,5	9,5	20,2	31,5	47,2	28,7		
		kPa	5	1,6	7,0	6,7	16,5	18,5	33,1	25,5		
		kPa	4	1,5	5,6	5,9	13,5	13,6	25,2	23,7		
		kPa	3	1,2	3,8	4,6	11,1	13,1	19,1	19,6		
		kPa	2	1,0	2,4	2,8	9,0	9,9	16,5	13,7		
		kPa	1	0,9	2,4	2,4	7,3	8,7	13,6	7,5		
Portata aria		m³/h	6	411	531	528	812	813	867	1231		
		m³/h	5	348	459	451	682	685	708	1126		
		m³/h	4	289	390	395	576	579	578	1064		
		m³/h	3	244	343	346	495	500	489	925		
		m³/h	2	210	271	263	420	429	413	726		
		m³/h	1	185	227	224	360	368	357	495		
Livello di potenza sonora	(E)	dB(A)	6	53	51	51	56	57	57	68		
		dB(A)	5	49	47	47	51	52	52	68		
		dB(A)	4	45	44	44	47	47	46	66		
		dB(A)	3	41	41	40	43	42	42	64		
		dB(A)	2	39	34	33	39	38	38	59		
		dB(A)	1	32	30	30	37	34	35	52		
Livello di pressione sonora	(E)	dB(A)	6	44	42	42	47	48	48	59		
		dB(A)	5	40	38	38	42	43	43	59		
		dB(A)	4	36	35	35	38	38	37	57		
		dB(A)	3	32	32	31	34	33	33	55		
		dB(A)	2	30	25	24	30	29	29	50		
		dB(A)	1	23	21	21	28	25	26	43		

Con mobile		20	30	40	50	60	70	80
Lunghezza	L	mm	860	1060	1060	1260	1260	1460
Altezza	H	mm	480	480	480	480	480	585
Profondità	P	mm	225	225	225	225	225	225

